Washing machine for the home

Spirit 540





Product No 8540.2C

Model with large 4.3" colour display, 1–8 kg load capacity and LED drum lighting. Short Swiss wash programmes from 20 to 90°C, cleanJet Technology, programme groups: Sportswear, Homecare, Businesswear, Antibac, Softcare. Time preset for up to 24 hours.

- Express wash from 20 min. from 20 to 90°C
- Favourites
- cleanJet programmes 20-90°C
- Cotton Powerclean 40/60°C, 57 min.
- 30°C Quickwash, 15 min.
- Dirt sensor, load and dosage indicator
- 3D washing drum
- Chrome-plated door
- Caustic tank in chrome steel
- Aquastop
- · Available in different colour versions

Load capacity: 1–8 kg Spin speed: 1600–200 rpm

Features

- Large 4.3" colour display
- 24 languages can be selected
- 3D washing drum
- Noise insulation: Supersilent Plus
- cleanJet technology
- LED drum lighting
- Dirt sensor
- Load detection and detergent dosing display
- Water level adjustment for partial load
- Programme progress and remaining time display
- Time preset for up to 24 hours
- Individual appliance settings: e.g. additional rinse cycle
- Signal tone with variable volume at programme end
- · Caustic tank in chrome steel
- Door opening angle 180°, large opening \varnothing 34 cm
- · Door hinge right or left
- · Chrome-plated door

Programmes

- Short Swiss wash programmes 20–90°C (2 heating elements)
- Express programmes at all temperatures from 20 min.
- **Programme groups** Sportswear, Homecare, Businesswear, Antibac, Softcare
- Favourites for your 6 favourite programmes
- Standard programmes Cotton 20–90°C, Cotton Powerclean 40/60°C, Easy Care 30–60°C, Handwash 20°C, Wool 30°C, Silk 30°C, Delicates 40°C, Mixed laundry 40°C, 15 min. Quickwash 30°C, Shirts/Blouses Iron-Finish 40°C, Sportswear, Jeans, Curtains, Impregnating, Baby laundry 40/70°C, Plastic toys, Autoclean (machine cleaning programme)
- Eco programmes Eco 40-60
- Programme options Supersilent for extremely quiet washing, Express, Pre-wash, Intensive (stains), Rinse+, Temperature reduction, Spin speed, Rinsing stop, Soaking

Swiss wash programmes

 Wool 30°C 	40 min.
 Quickwash 30°C 	15 min.
 Mixed laundry 40°C 	59 min.
 Cotton 40°C 	61 min.
 Cotton Express 40°C 	25 min.
• Cotton 60°C	71 min.
 Cotton Powerclean 40/60°C 	57 min.

Safety systems

- Child lock, double-walled door glass
- Aquastop, foam monitoring, imbalance detection
- Control display for water intake/drainage

Model

• White (available in different colour versions)

Options

- smartHeat (hot water connection) or soft water/rainwater connection
- Plinth drawer (white) H: 30.5 cm

Installation and connections

Height/width/depthEmpty weight85/60/67 cm92 kg

• Electrical connection 400 2N~ 50 Hz, 4.0 kW, 10 A

230 1N~ 50 Hz, 2.1 kW, 10 A *230 1N~ 50 Hz, 3.5 kW, 16 A

Water connection
 Water pressure
 Water drainage
 Pressure hose ¾"
 1–10 bar
 Drain hose LW 21
 *Appliance version

*Appliance version «S» with type 23 plug



Colour versions washing machine Spirit 540







Anthracite 8540.2CU



Solid Gold 8540.2CU1



Ever Rose 8540 2CU2



Titan Rock 8540.2CU3



Chrome 8540.2CL1

Attention: Colour may vary due to lighting conditions, screen or print qualities. Inspect the product in a showroom or order relevant material samples from your advisor.

Technical data washing machine Spirit 540

Schutthess Schutthess Schutthess Schutthess Spirt \$40
Product number
Agriculty Machine type Sategory / Machine type Sefficiency and consumption** Interry efficiency class / Efficiency index A to 6/EEI A/50,5 Interry consumption per operating cycle Why 0.26 W
sategory / Machine type Efficiency and consumption P Front loader Efficiency and consumption P Front loader Efficiency and consumption P Front loader RWh 0.46 NWh 0.4
A to G/EEI A/50,5
intergr efficiency class / Efficiency index intergr consumption per operating cycle
intergr efficiency class / Efficiency index intergr consumption per operating cycle
Intergret consumption per operating cycle
Standby mode / time preset / networked standby mode ### Act Consumption per operating cycle 1
Valer consumption per operating cycle Performance characteristics 10 prinning efficiency class from A to 6 Asamum spin speed (full /half / quarter load) mpm Sestidual mostures 2 (full /half / quarter load) mpm Sestidual mostures 2 (full /half / quarter load) mpm Sestidual mostures 2 (full /half / quarter load) mpm Sestidual mostures 2 (full /half / quarter load) mpm Sestidual mostures 2 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 3 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half / quarter load) mpm Sestidual mostures 4 (full /half
performance characteristics by pinning efficiency class spinning effect spinning effect efficiency index spinning effect efficiency index class spinning effect efficiency developed by the spinning effect efficiency index class spinning effect efficiency developed by the spinning efficiency developed by the s
Spinning efficiency class
Assimum spin speed (full /half / quarter load)
Nesidual moisture (full / half / quarter load) % 44/44/4 Mashing efficency index 1.04 Mashing efficency index 1.04 Mashing efficency index 1.04 Mashing efficency index 1.04 Mashing efficency 1.04 Mashing efficency 1.04 Mashing effect
Vashing efficiency index Injust temperature in the laundry (full half / quarter load) Vashing efficiency index Injust temperature in the laundry (full half / quarter load) Vashing effect Vashing effect Vashing effect Vashing effect Vashing effect Vashing effect Vashing efficiency (full half / quarter load) Vashing efficiency (full half / quar
Rinsing effect G/Ng Green effect G/Ng Green effect G/Ng Rinsing effect G/Ng Rinsing effect Rinsing effet G/Ng Rin
signest temperature in the laundry (full / half / quarter load) "C 36/30/24 Programme duration (full / half / quarter load) h.min 35/24.8/2.88 Numatic switch-off time min 5 Numatic switch-off time Numatic switch-of
Programme duration (full / half / quarter load)
Subtractic switch-off time
A
Victor V
Index-counter unit
Index-counted unit with worktop
Con-mounted unit with worktop Con-mounted unit under worktop Con-mounted under worktop Con-m
Floor-mounted unit under worktop Joor hinge 31
Aborn hinge 30 Machine dimensions 41 Height cm 85 Width cm 60 Depth (including wall distance) cm 60 Depth (including wall distance) cm 67 Depth with open door (including wall distance) cm 110 Adjustable height mm 0–10 Including wall distance) cm 110 Adjustable height mm 0–10 Including wall distance) cm 110 Adjustable height mm 0–10 Including wall distance) wm 0–10 Including wall distance
Height
Height
Width cm 60 Depth (including wall distance) cm 67 Depth (including wall distance) cm 85.5 Depth with open door (including wall distance) cm 110 Depth with open door (including wall door (inclu
Depth (including wall distance) cm 67 Inder-counter height cm 85. Depth with open door (including wall distance) cm 110 Indepth with open door (including wall door (inclu
Under-counter height cm 85.5 Depth with open door (including wall distance) cm 110 Midjustable height mm 0–10 Empty weight kg 92 Electrical connection* Voltage V/Hz 400 2N~/230 1N~ foliage V/Hz 400 2N~/230 1N~ fo
Adjustable height mm 0-10 Impty weight kg 92 Ielectrical connection 5 V/Hz 400 2N-/230 1N- 4,0/2,1/3,5* Protection A 10/10/16* Water connected loads kW 4,0/2,1/3,5* Protection A 10/10/16* Water connection
Electrical connection 5 Clause VHz 400 2N~/230 1N~ Connected loads kW 40/2,1/3,5* Cortection A 10/10/16* Water connection Versure hose GW m • Connectable to cold/hot water • Option Vater pressure bar 1-10 Safety and customer service Country of origin CH Varranty years Varranty years Varranty years Country of Origin CH Varranty years Country of Origin CH Varranty years Country of Country of CH Varranty years Country of Country of CH Varranty years Country of COUNTRY
Clectrical connection* Voltage V/Hz V/Hz V/L/2.17.3.5* Connected loads kW V/L/2.17.3.5* Connected loads kW V/L/2.17.3.5* Connected loads kW V/L/2.17.3.5* Connection A 10/10/16* Water connection Pressure hose GW m • • Option Vater pressure bar 1 – 10 Safety and customer service Country of origin CH Schulthess Maschinen AG Schulthess Maschinen AG Schulthess Maschinen AG Sana and address of supplier Gayanty years 2 Equipment Washing programmes VOC Wool min 40 VOC Quickwash min 15 VOC Wool min 59 VOC Cotton Mixed laundry min 59 VOC Cotton min 61 VOC Cotton min 61 VOC Cotton Express min 25 VOC Cotton Powerclean min 71 VOC Cotton Powerclean min 57 Favourites for your 6 favourite programmes Voca detection / Dirt sensor Silent Motor Laustic tank in stainless steel • •
Voltage V/Hz 400 2N~/230 1N~ Connected loads KW 4,0 / 2,1 / 3,5 * Protection A 10/10/16 * Water connection Pressure hose G%" m • Connectable to cold/hot water •/Option Water pressure bar 1–10 Safety and customer service Country of origin CH Same and address of supplier 5330 Cham ZG Warranty years 2 Equipment Washing programmes 10°C Wool min 40 10°C Quickwash min 50°C Culckwash min 59 10°C Cotton Express min 25 10°C Cotton Express min 25 10°C Cotton Express min 25 10°C Cotton Powerclean min 57 10°C Odd effective for your 6 favourite programmes 10°C Cotton Powerclean min 57 10°C dedection / Dirt sensor 10°C austic tank in stainless steel • 10°C austic tank in stainless steel
Aconnected loads kW 4,0/2,1/3,5* Protection A 10/10/16* Water connection Pressure hose G%" m • Connectable to cold/hot water • (Option Water pressure bar 1 – 10 Safety and customer service Country of origin CH Same and address of supplier 6330 Cham ZG Warranty years 2 Equipment Washing programmes 10°C Wool min 40 10°C Quickwash min 15 10°C Outcomed min 61 10°C Cotton Express min 25 10°C Cotton Express min 25 10°C Cotton Powerclean min 57 avourites for your 6 favourite programmes 10°C Motor Screen for up to 24 hours encounter of the content of the conten
A 10/10/16* Nater connection Pressure hose G¾" m • Connectable to cold/hot water
Water connection Pressure hose G%" m • Option Vater pressure Vater value
Pressure hose 6%" Connectable to cold/hot water Vater pressure Description Safety and customer service Country of origin CH Schulthess Maschinen AG Sanuthess Maschine
Fornectable to cold/hot water Water pressure Safety and customer service Country of origin CH Schulthess Maschinen AG 6330 Cham ZG Warranty Vears Sequipment Washing programmes On °C Wool On °C Quickwash On °C Quickwash On °C Cotton Inin
Water pressure bar 1–10 Safety and customer service Country of origin CH Schulthess Maschinen AG 6330 Cham ZG Warranty years 2 Saguipment Washing programmes Washing programmes Washing programmes Washing delaundry min 15 40°C Quickwash min 15 40°C Cotton Express min 61 40°C Cotton Express min 25 40°C Cotton Express min 25 40°C Cotton Powerclean min 57 Tavourites for your 6 favourite programmes Ime preset for up to 24 hours Couled the stainless steel of the stainless steel of the stainless steel of the scale of the s
Safety and customer service Country of origin CH Schulthess Maschinen AG 6330 Cham ZG Warranty years 2 Equipment Washing programmes 80 °C Wool CO Quickwash CO C Quickwash CO C Cotton CO E Cotton CO E Cotton CO C C C Cotton CO C C C Cotton CO C C C C C C C C C C C C C C C C C C
Country of origin CH Schulthess Maschinen AG 6330 Cham ZG Warranty Vears Zeguipment Washing programmes 80 °C Wool min 40 80 °C Quickwash min 15 80 °C Mixed laundry min 59 80 °C Cotton Express min 61 80 °C Cotton Express min 25 80 °C Cotton Powerclean min 57 Tavourites for your 6 favourite programmes Ime preset for up to 24 hours Caustic tank in stainless steel CH Schulthess Maschinen AG 6330 Cham ZG CH Schulthess Maschinen AG 6330 Cham ZG AB AD CH Schulthess Maschinen AG 6330 Cham ZG AB CH Schulthess Maschinen AG 6330 Cham ZG AD AD AD AD CO COLOR FINE Schulthess Maschinen AG 6330 Cham ZG AD AD AD AD COLOR FINE Schulthess Maschinen AG 6330 Cham ZG AD AD AD AD AD COLOR Schulthess Maschinen AG 6330 Cham ZG AD AD AD AD AD COLOR Schulthess Maschinen AG 6330 Cham ZG AD AD AD AD AD COLOR Schulthess Maschinen AG 6330 Cham ZG AD AD AD AD AD AD COLOR Schulthess Maschinen AG 6330 Cham ZG AD AD AD AD AD AD COLOR Schulthess Maschinen AG 6330 Cham ZG AD AD AD AD AD AD AD AD AD A
Schulthess Maschinen AG 6330 Cham ZG Varranty Vears 2 Equipment Washing programmes 10 °C Wool Min 40 00 °C Quickwash Min 59 10 °C Cotton Min 61 10 °C Cotton Express Min 25 10 °C Cotton Express Min 71 10 °C Cotton Powerclean Min 57 Mayorites for your 6 favourite programmes Mayorites for your 6 favourites for your 6 favourites for your 6 favourites fa
Aame and address of supplier Warranty Years Equipment Washing programmes 10 °C Wool On °C Quickwash On °C Quickwash On °C Quickwash On °C Cotton Min 61 On °C Cotton Express On °C Cotton On 10 On °C Cotton Express On °C Cotton On 10 On °C Cotton Powerclean Favourites for your 6 favourite programmes On °C Cotton In The
Warranty years 2 Equipment Washing programmes 10 °C Wool min 40 10 °C Quickwash min 15 10 °C Cutton Express min 25 10 °C Cotton Express min 25 10 °C Cotton Fowerclean min 57 Favourites for your 6 favourite programmes 10 °C Cotton Forest for up to 24 hours 10 °C Caustic tank in stainless steel •
Equipment Vashing programmes 10 °C Wool min 40 10 °C Quickwash min 15 10 °C Quickwash min 59 10 °C Cotton 10 °C Cotton min 61 10 °C Cotton Express min 25 10 °C Cotton Powerclean min 71 10 °C Cotton Powerclean min 57 Tavourites for your 6 favourite programmes Time preset for up to 24 hours 10 °C detection / Dirt sensor for up to 24 hours 10 °C Caustic tank in stainless steel e
Vashing programmes 10 °C Wool min 40 10 °C Quickwash min 15 10 °C Mixed laundry min 59 10 °C Cotton min 61 10 °C Cotton Express min 25 10 °C Cotton Express min 71 10 °C Cotton Powerclean min 57 Favourites for your 6 favourite programmes for up to 24 hours on the control of the contr
80 °C Wool min 40 80 °C Wised Quickwash min 15 80 °C Quickwash min 15 80 °C Quickwash min 59 80 °C Cotton Wised Quickwash min 61 80 °C Cotton Express min 25 80 °C Cotton Express min 25 80 °C Cotton Min 71 80 °C Cotton Powerclean min 57 80 °C Cotton
10 °C Quickwash min 15 10 °C Mixed laundry min 59 10 °C Cotton Min 61 10 °C Cotton Express min 25 10 °C Cotton Express min 25 10 °C Cotton Powerclean min 71 10 °C / 60 °C Cotton Powerclean min 57 10 °C may be seen a considerate of the seen and the see
40 °C Mixed laundry min 59 61 60 °C Cotton min 61 61 61 60 °C Cotton Express min 25 60 °C Cotton Express min 71 60 °C Cotton Powerclean min 57 62 60 °C Cotton Powerclean min 57 62 60 °C Cotton Powerclean min 57 62 60 °C Job Cotton Powerclean min 57 60 °
40 °C Cotton
40 °C Cotton Express min 25 on 71 on
50 °C Cotton min 71 10 °C / 60 °C Cotton Powerclean min 57 Favourites for your 6 favourite programmes
ST
Favourites for your 6 favourite programmes Time preset Load detection / Dirt sensor For up to 24 hours -/• For up to
ime preset for up to 24 hours oad detection / Dirt sensor illent Motor Caustic tank in stainless steel
Silent Motor • Caustic tank in stainless steel • • • • • • • • • • • • • • • • • •
Caustic tank in stainless steel •
ELL GRUM MODUNG
Heating elements 2
Automatic door opening • in the front, Ø 34
Connection cable m 1,6
nlet hose with fine filter m 1,5
Prain hose with bend m 1.5
TIII 1,J
aundry bags (for plastic toys, lingerie etc.)

Explanations • available - not available

- Consumption values were determined according to the valid EN 60456 standard. These values are weighted values for full/half/quarter loads, based on the Eco 40–60 programme.
- 2) Dewatering degree 100% means that in 1 kg of laundry (dry weight) 1 kg of water is still bound after spinning. The lower the % value, the less damp the laundry is.
- Door hinge I = left, r = right, w = changeable. Example I/w corresponds to delivery condition door hinge left, hinge changeable.
- For under-counter units, niche dimensions.
 Further dimensions are given in the brochures.
- Information on switching options is, where applicable, included in the brochures.
- Values determined in the Eco 40–60 programme at nominal capacity.

The standardised product declaration corresponds to the declaration of the Swiss Professional Association for Electrical Appliances in Household and Industry (FEA) in cooperation with consumer organisations. The product declaration is based on the standards of the IEC International Electrotechnical Commission (Technical Commission TC 59).

Note: table information as of 03/2022, subject to further developments.