



topLine 8940

- Load capacity: 7 kg
- Large 4.3" colour display
- Drum vanes for 3D-Washing
- Drum capacity: 60 l
- Spin speed: 1600 rpm
- g factor 690
- Residual moisture 43%
- With drain valve or drain pump
- Language selection button
- profiClean programme button
- 94 profiClean and 24 freely programmable slots
- USB-interface for PC software
- Door hinge right or left

topLine 9240

- Load capacity: 8 kg
- Large 4.3" colour display
- Drum vanes for 3D-Washing
- Drum capacity: 70 l
- Spin speed: 1600 rpm
- g factor 690
- Residual moisture 43%
- With drain valve or drain pump
- Language selection button
- profiClean programme button
- 94 profiClean and 24 freely programmable slots
- USB-interface for PC software
- Door hinge right or left
- Anthracite or chrome steel finish

Company or brand name	Schulthess	
Type of appliance	Washing machine topLine 8940	Washing machine topLine 9240
Type or sales description	topLine 8940	topLine 9240
Product number		
Model with drain pump (P)	8940.2EPU	9240.2EPU
Model with drain valve (V)	8940.2EUW	9240.2EUW
Application features		
Load capacity	max. kg 7	8
Drum capacity	l 60	70
Spinning speed	max. rpm 1600	1600
g factor	g 690	690
Residual moisture ¹⁾	% 43	43
Structural design		
Footed appliance with work surface	•	•
Door hinge ²⁾	r/l/w	r/l/w
Dimensions		
Height	cm 90	90
Width	cm 63	63
Depth including distance from wall	cm 72	72
Depth with door open (front loader)	cm 116	116
Height (adjustable)	cm 1	1
Weight when empty	kg 100	102
Equipment		
Detergent tank and drum	chrome-nickel steel	chrome-nickel steel
Loading opening	∅ cm 34 / 180°	34 / 180°
Automatic door opening	•	•
Connecting cable	m 1.6	1.6
Drain		
– Drain hose with benda, only model (P)	m 1.5	1.5
– Model with drain pump (P)	∅ mm 21	21
– Model with drain valve (V)	∅ mm 50	50
Electric power and water supply		
Electrical connection ³⁾		
Voltage / connected loads / fuse	400 V 2N~ / 50Hz / 4,6kW / 10A 230 V 1N~ / 50Hz / 2,3kW / 10A	400 V 3N~ / 50Hz / 4,6kW / 10A 400 V 2N~ / 50Hz / 4,6kW / 10A 230 V 1N~ / 50Hz / 2,5kW / 13A 230 V 1N~ / 50Hz / 2,3kW / 10A
Water connection		
– Pressure hose G ¾" with fine filter	m 1.5	1.5
– Can be connected to cold water / hot water	cold water / hot water 70 °C	cold water / hot water 70 °C
– Water pressure	bar 1–10	1–10
Options		
		– Execution in chrome steel
	– Door hinge left	– Door hinge left
	– Drain valve or drain pump	– Drain valve or drain pump
	– USB-interface for PC software	– USB-interface for PC software
	– RFD-Card-System	– RFD-Card-System
	– Connection for 8 liquid detergents with dosing pump	– Connection for 8 liquid detergents with dosing pump
	– Machine plinth	– Machine plinth
	– Machine plinth with lint trap drawer	– Machine plinth with lint trap drawer
Safety and service		
Conforms to the European Machinery Directive	2006/42/EC	2006/42/EC
Country of origin	Switzerland	Switzerland
Guarantee	1 year	1 year
Service by	Schulthess Maschinen AG	
Name and address of supplier	Schulthess Maschinen AG, CH-8633 Wolfhausen/ZH	

Explanations:

– Available or yes • Not available or no

1) Values determined in the 60°C cotton programme.

2) Door hinge: l = left, r = right, w = can be changed

Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.

3) Information on switchover options can be found in the installation instructions, where required.

Note: State of the table details as 03.2021, subject to further developments.